



## **FULLY ELECTRIC BLOW MOULDING MACHINE** **High performance extrusion blow moulding machine** **for the production of High Quality Plastic Packaging**

- Single or Double station, continuous extrusion
- Customizable following your needs
- Long-stroke shuttle machines upto 2000mm mould carriage stroke, 28 parisons
- Multi-layer options upto 7 layers, 16 parisons
- Additional options and accessories available such as IML, angular neck
- Outstanding performance, productivity and reliability
- Top product quality through proprietary extrusion technology
- Integrated after cooling and deflashing unit
- Standard machine components by well-known German / European makers
- Easy to use control system
- Compact, long life and easy maintenance designs
- Remote service via Internet



## High Outputs Range Machines

\*Sample models and specifications. We do provide various other machine sizes and configurations

Blow moulding machine Type		SBS 1500S * Single Station IML	SBS 1800D * Double Station
Product volume	ml	4000	5000
Machine output (500ml, 35g)	pcs/h	≥ 800	≥ 1,700
Clamping force	kN	500	500
Mould width	mm	1490	1770
Mould thickness	mm	2 x 200	2 x 200
Mould height	mm	425	425
Mould opening stroke	mm	360	360
Main Extruder Diameter/Length		70/26D, 100/26D	120/26D, 120/26D
Melting capacity	kg/h	180, 300	350, 350
Extrusion Head	layers	6	6
Cavity		6	6
Total installed power	kW	315	500
Average power consumption*	kW	126	247
Air pressure	bar	6	6
Air consumption	L/min	1500	1500
Mould cooling temperature	°C	8	8
Machine width	mm	5330	10800
Machine length	mm	8700	8800
Machine height	mm	5000	5500

### SAB PLASTMACH CO., LTD.

134 M4,T.Tub Khang, A.Khao Yoi,  
Phetchaburi 76140, Thailand

Phone: +6632.797.444  
Fax: +6632.797.451  
[www.sabmann.com](http://www.sabmann.com)

[sab@sabplas.com](mailto:sab@sabplas.com)  
[sabmann-ebm@t-online.de](mailto:sabmann-ebm@t-online.de)